



ADDENDUM - 1

SI No	Clause	Existing	Changed To
1	Technical Specifications - Point no 4	System to have minimum Two controllers, configured in Active-Active HA Pair with automatic failover. The failure of one controller should have no impact on the device's performance.	System to have minimum Two controllers, configured in Active-Active HA Pair with automatic failover. In the event of failure of one controller, the surviving controller is expected to independently sustain the defined performance of 250,000 IOPS without any degradation in application performance during failover or takeover operations.
2	Technical Specifications - Point no 38	System must provide immutable snapshots and native WORM volumes for compliance.	System must have immutable snapshots features.
3	Technical Specifications - Point no 40	Solution must comply with all regulatory regulations (RBI, IRDAI, SEC 17a-4, MeITy, etc.).	Solution must comply with all regulatory regulations (RBI, IRDAI, MeITy, etc.).
4	Technical Specifications - Point no 36	Replication must support both block and file data, encrypted end-to-end.	This clause stands deleted.
5	Technical Specifications - Point no 3	The system must be all-flash NVMe based for enterprise-class performance with data Deduplication, Compression support available. (End to end NVMe)	The system must be all-flash NVMe based for enterprise-class performance with data Deduplication, Compression support available and enabled on Day 1. (End to end NVMe)

Anil Kumar Reddy
Chief Manager,
IT Department.

